



**Pull Tabs**

| A<br>DIAMETER | B<br>MAX LENGTH* | A<br>DIAMETER         | B<br>MAX LENGTH* |
|---------------|------------------|-----------------------|------------------|
| I N C H E S   |                  | M I L L I M E T E R S |                  |
| .187          | .750             | 4.75                  | 19.05            |
| .207          | 1.500            | 5.26                  | 38.11            |
| .240          | 1.500            | 6.10                  | 38.11            |
| .250          | 1.500            | 6.35                  | 38.11            |
| .300          | 1.500            | 7.62                  | 38.11            |
| .312          | 1.500            | 7.93                  | 38.11            |
| .360          | 1.500            | 9.15                  | 38.11            |
| .375          | 1.500            | 9.53                  | 38.11            |
| .437          | 1.500            | 11.10                 | 38.11            |
| .490          | 1.500            | 12.45                 | 38.11            |
| .521          | 1.500            | 13.24                 | 38.11            |
| .552          | 1.500            | 14.02                 | 38.11            |
| .600          | 1.500            | 15.24                 | 38.11            |
| .615          | 1.500            | 15.63                 | 38.11            |
| .677          | 1.500            | 17.20                 | 38.11            |
| .740          | 1.500            | 18.80                 | 38.11            |
| .843          | 1.500            | 21.42                 | 38.11            |
| .990          | 1.500            | 25.15                 | 38.11            |
| 1.250         | 3.500            | 31.76                 | 88.92            |



**Vented Pull Tabs**

| PART<br>NUMBER | FITS TUBE SIZE        |                |
|----------------|-----------------------|----------------|
|                | DIAMETER              | WALL THICKNESS |
|                | I N C H E S           |                |
| VPT-1          | 3/16                  | 1/16           |
| VPT-25         | 1/4                   | 1/16           |
| VPT-3          | 3/8                   | 1/16           |
| VPT-4          | 3/8                   | 3/32           |
| VPT-5          | 1/2                   | 3/32           |
| VPT-6          | 1/2                   | 1/8            |
| PART<br>NUMBER | FITS TUBE SIZE        |                |
|                | DIAMETER              | WALL THICKNESS |
|                | M I L L I M E T E R S |                |
| VPT-1          | 4.76                  | 1.58           |
| VPT-25         | 6.35                  | 1.58           |
| VPT-3          | 9.53                  | 1.58           |
| VPT-4          | 9.53                  | 2.38           |
| VPT-5          | 12.70                 | 2.38           |
| VPT-6          | 12.70                 | 3.18           |

Wall thickness "C" is measured approximately 1/4" from the open end. Nominal wall is .045 ± .010

**\*The Lengths listed above are maximum lengths.** Minimum length is 1/4". Lengths can be adjusted in 1/16" increments up to the maximum. Length is measured from the inside wall, not to the center. Length tolerance is ± 1/16".

**Grab Tabs**

**GRAB TABS**

New tab design provides more surface area to grab. The ergonomic finger tab is perfect for continuous removal and installation processes.

Available in standard and high-temperature formulations.

Pull Tabs are ideal for:

- Thread protectors
- Paint masks
- Shipping caps
- Dust caps

| A<br>DIAMETER | B<br>MAX LENGTH* | A<br>DIAMETER         | B<br>MAX LENGTH* |
|---------------|------------------|-----------------------|------------------|
| I N C H E S   |                  | M I L L I M E T E R S |                  |
| .215          | 2.000            | 5.46                  | 50.81            |
| .240          | 2.000            | 6.10                  | 50.81            |
| .250          | 2.000            | 6.35                  | 50.81            |
| .303          | 2.000            | 7.70                  | 50.81            |
| .313          | 2.000            | 7.95                  | 50.81            |
| .365          | 2.000            | 9.27                  | 50.81            |
| .386          | 2.000            | 9.81                  | 50.81            |
| .427          | 2.000            | 10.85                 | 50.81            |
| .490          | 2.000            | 12.45                 | 50.81            |
| .521          | 2.000            | 13.24                 | 50.81            |
| .530          | 2.000            | 13.47                 | 50.81            |
| .552          | 2.000            | 14.02                 | 50.81            |
| .615          | 2.000            | 15.63                 | 50.81            |
| .677          | 2.000            | 17.20                 | 50.81            |
| .735          | 2.000            | 18.67                 | 50.81            |
| .740          | 2.000            | 18.80                 | 50.81            |
| .797          | 2.000            | 20.25                 | 50.81            |
| .860          | 2.000            | 21.85                 | 50.81            |
| .937          | 2.000            | 23.81                 | 50.81            |
| .985          | 2.000            | 25.03                 | 50.81            |
| 1.060         | 2.000            | 26.93                 | 50.81            |
| 1.125         | 2.000            | 28.58                 | 50.81            |
| 1.250         | 2.000            | 31.76                 | 50.81            |

There are new sizes and styles of vinyl parts becoming available on a regular basis, please contact our Sales Department.

16 For fast service and free samples, call: 1-800-668-3235 Fax: 1-905-791-3178 or Email: sales@capsnplugs.com